



Touch Chem (M) Sdn Bhd (449639-v)

22, Jalan Anggerik Mocara 31/64,
Kota Kemuning, 40460, Shah Alam,
Selangor Darul Ehsan, Malaysia.

Tel : +603-5121 8802

Fax : +603-5122 1973

Touch DF 4001

Modified Paraffin Mineral Oil based defoamer for water based coating

Properties

Active Ingredient	:	100%
Appearance	:	Milky solution
Density	:	0.86 – 0.88 g/cm ³

Description

Touch DF 4001 is a specially modified paraffin mineral oil based defoamer for all type of water based emulsion paint. The defoamer is stable upon storage, resistant to yellowing from ultra-violet radiation and does not influence color acceptance and color development in tinted systems.

The advantages of **Touch DF 4001** are as below:

- Does not have color that influence the final paint color.
- Stable upon storage.
- Does not influence color acceptance and color development.
- No influence on paint physical and chemical properties

Touch DF 4001 is a better defoamer comparing to our last version defoamer **Touch DF 4000**. It have 2-3 times better defoaming properties.

Recommended For Use

Touch DF 4001 is recommended for all water based emulsion paint. It is very easy to use and can be incorporated during grinding as well as after mix. If incorporated in grinding phase, make sure that 0.1 – 0.2% of **Touch DF 4001** should be added additionally at the let down stage.

Dosage

0.1 – 0.5% based on total formulation.

Storage

Touch DF 4001 is recommended to store in cool and dry place. Keep out of rain and direct sunlight.

Packaging

20kg & 170 kg non-returnable metal Container.